



**Material** : Scroll Housing & Impellor made of Galvanized Sheet Steel with Powder Coating  
**Type of protection** : IP44  
**Bearing** : Ball Bearings  
**Operation Mode** : S1

**Protection** : Thermal Overload Protector (TOP) wired Internally  
**Motor Insulation Class** : F  
**Direction of Rotation** : Anticlockwise, see on the leads.  
**Amb. Temp** : -40 ~ +60°C  
**Approvals** : CCC, CE, UL

| TYPE                    | MOTOR          | VOLTAGE (VAC) | FREQUENCY (Hz) | Speed | AIRFLOW (m³/h) | AIRFLOW (CFM) | SPEED (rpm) | POWER (W) | CURRENT (A) | NOISE (Lp:dB(A)) | CAPACITOR (µF/V) |
|-------------------------|----------------|---------------|----------------|-------|----------------|---------------|-------------|-----------|-------------|------------------|------------------|
| DH230A2-AG5-01 (FS 230) | AM068A2-AG5-01 | 230           | 50             | H     | 2630           | 1548          | 780         | 734       | 3.2         | 69               | 16/450           |
|                         |                |               |                | M     | 1950           | 1148          | 600         | 465       | 2.1         | 61               |                  |
|                         |                |               |                | L     | 1620           | 954           | 500         | 330       | 1.5         | 57               |                  |

